

Retail Guide

Uyuni 2020.09

September 17, 2020

Table of Contents

Components2The Uyuni Server2Build Hosts2Branch Servers2Point-of-Service Terminals2Fitting It All Together3Installation5Requirements5Install with the Unified Installer6Network Architecture11Setting up13Deploying Terminals17Deploy Terminals17Deploy Terminals21Offline Use30
Build Hosts2Branch Servers2Point-of-Service Terminals2Fitting It All Together3Installation5Requirements5Install with the Unified Installer6Network Architecture11Setting up13Deploying Terminals17Deploy Terminals - Other Methods21
Branch Servers2Point-of-Service Terminals2Fitting It All Together3Installation5Requirements5Install with the Unified Installer6Network Architecture11Setting up13Deploying Terminals17Deploy Terminals - Other Methods21
Point-of-Service Terminals2Fitting It All Together3Installation5Requirements5Install with the Unified Installer6Network Architecture11Setting up13Deploying Terminals17Deploy Terminals17Deploy Terminals - Other Methods21
Fitting It All Together3Installation5Requirements5Install with the Unified Installer6Network Architecture11Setting up13Deploying Terminals17Deploy Terminals17Deploy Terminals21
Installation5Requirements5Install with the Unified Installer6Network Architecture11Setting up13Deploying Terminals17Deploy Terminals17Deploy Terminals - Other Methods21
Requirements.5Install with the Unified Installer.6Network Architecture.11Setting up.13Deploying Terminals.17Deploy Terminals.17Deploy Terminals - Other Methods.21
Install with the Unified Installer.6Network Architecture.11Setting up.13Deploying Terminals.17Deploy Terminals.17Deploy Terminals - Other Methods.21
Network Architecture11Setting up13Deploying Terminals17Deploy Terminals17Deploy Terminals - Other Methods21
Setting up13Deploying Terminals17Deploy Terminals17Deploy Terminals - Other Methods21
Deploying Terminals17Deploy Terminals17Deploy Terminals - Other Methods21
Deploy Terminals 17 Deploy Terminals - Other Methods 21
Deploy Terminals - Other Methods
Offline Use 30
On mile 0.50
Introduction to Retail Formulas 32
Branch Server Formulas
Partitioning and Image Deployment Formula
Administration 34
Mass Configuration
Delta Images
Retail Migration 40
Upgrade Uyuni for Retail Branch Server
What Next? 41
More Documentation
Support
GNU Free Documentation License 42

Retail Guide Overview

Publication Date: 2020-09-17

Uyuni for Retail 2020.09 is an open source infrastructure management solution, optimized and tailored specifically for the retail industry. It uses the same technology as Uyuni, but is customized to address the needs of retail organizations.

Uyuni for Retail is designed for use in retail situations where customers can use point-of-service terminals to purchase or exchange goods, take part in promotions, or collect loyalty points. In addition to retail installations, it can also be used for novel purposes, such as maintaining student computers in an educational environment, or self-service kiosks in banks or hospitals.

Uyuni for Retail is intended for use in installations that include servers, workstations, point-of-service terminals, and other devices. It allows administrators to install, configure, and update the software on their servers, and manage the deployment and provisioning of point-of-service machines.

This guide provides an overview of Uyuni for Retail, and its initial installation and setup. It should be read in conjunction with the Uyuni documentation suite, available from https://documentation.suse.com/suma.

For more information about managing your Uyuni for Retail environment, or to find out where to get help, see [**Retail > Retail-next >**].

Components

Uyuni for Retail is made up of various components. For more on how these components work together, see retail-network-arch.pdf.

The Uyuni Server

The Uyuni server contains information about infrastructure, network topology, and everything required to automate image deployment and perform day-to-day operations on branches and terminals. This can include database entries of registered systems, Salt pillar data for images, image assignments, partitioning, network setup, network services, and more.

Build Hosts

Build hosts can be arbitrary servers or virtual machines. They are used to securely build operating system images.

For more information on build hosts, see [Administration > Image-management >].

Branch Servers

Branch servers should be physically located close to point-of-service terminals, such as in an individual store or branch office. Branch servers provide services for PXE boot, and act as an image cache, Salt broker, and proxy for software components (RPM packages). The branch server can also manage local networking, and provide DHCP and DNS services.

Point-of-Service Terminals

Point-of-Service (POS) terminals can come in many different formats, such as point-of-sale terminals, kiosks, digital scales, self-service systems, and reverse-vending systems. Every terminal, however, is provided by a vendor, who set basic information about the device in the firmware. Uyuni for Retail accesses this vendor information to determine how best to work with the terminal in use.

In most cases, different terminals will require a different operating system (OS) image to ensure they work correctly. For example, an information kiosk has a high-resolution touchscreen, where a cashier terminal might only have a very basic display. While both of these terminals require similar processing and network functionality, they will require different OS images. The OS images ensure that the different display mechanisms work correctly.

Uyuni for Retail supports POS terminals that boot using both BIOS and UEFI. For UEFI booting terminals, you will need to configure the EFI partition in the Saltboot formula. For more information on EFI in the Saltboot formula, see [Salt > Formula-saltboot >].

Fitting It All Together

Uyuni for Retail uses the same technology as Uyuni, but is customized to address the needs of retail organizations.

Hardware Types

Because every environment is different, and can contain many different configurations of many different terminals, Uyuni for Retail uses hardware types to simplify device management.

Hardware types allow you to group devices according to manufacturer and device name. Then all devices of a particular type can be managed as one.

Branch System Groups

Uyuni for Retail uses system groups to organize the various devices in your environment.

Each branch requires a system group, containing a single branch server, and the POS terminals associated with that server. Each system group is identified with a Branch ID. The Branch ID is used in formulas and scripts to automatically update the entire group.

Salt Formulas

Uyuni for Retail uses Salt formulas to help simplify configuration. Formulas are pre-written Salt states, that are used to configure your installation.

You can use formulas to apply configuration patterns to your hardware groups. Uyuni for Retail uses the Saltboot formula, which defines partitioning and OS images for terminals.

You can use default settings for formulas, or edit them to make them more specific to your environment.

For more information about formulas, see [Retail > Retail-formulas-intro >].

Saltboot

Saltboot is a collection of tools and processes that are used to bootstrap, deploy and validate Uyuni for Retail terminals.

Saltboot consists of:

• Initialization:

The saltboot **initrd** is created during image building and is required for bootstrapping terminals.

• Saltboot state:

The Salt state that contains the logic for the entire saltboot process.

• Partitioning pillars:

The Salt pillar structure that describes how terminals are partitioned and what image is deployed on each terminal.

• Images and boot images pillars:

When the image building feature in Uyuni successfully builds an image that contains the saltboot initrd, the image and boot image Salt pillars are created.

The saltboot process involves the Uyuni Server, a terminal running the saltboot **initrd**, and the branch server providing the saltboot services to the terminal.

For a detailed diagram explaining how the saltboot boot process works, see [Retail > Retail-saltbootdiagram >].

Installation

Uyuni Retail Server and Uyuni Retail Branch Server are installed on top of openSUSE Leap.

Requirements

Before you install Uyuni for Retail, ensure your environment meets the minimum requirements. This section lists the requirements for a Uyuni for Retail installation. These requirements are in addition to the Uyuni requirements listed at [Installation > General-requirements >].



Uyuni for Retail is tested on x86_64 architecture.

Server Requirements

Table 1. Hardware Requirements for Uyuni Server

Hardware	Recommended	
CPU	Minimum 4 dedicated 64-bit CPU cores	
RAM:	Test Server Minimum 8 GB	
	Base Installation Minimum 16 GB	
	Production Server Minimum 32 GB	
Disk Space:	/ (root) 24 GB	
	/var/lib/pgsql Minimum 50 GB	
	/srv Minimum 50 GB	
	/var/spacewalk Minimum 50 GB per SUSE product and 360 GB per Red Hat product	

Branch Server Requirements

Table 2. Hardware Requirements for Branch Server

Hardware	Recommended	
CPU	Minimum 2 dedicated 64-bit CPU cores	
RAM:	Test Server Minimum 2 GB	
	Production Server Minimum 8 GB	
Disk Space:	/ (root) Minimum 24 GB	
	/srv Minimum 100 GB	
	/var/cache Minimum 100 GB	

Build Host Requirements

Table 3. Hardware Requirements for Build Host

Hardware	Recommended	
CPU	Multi-core 64-bit CPU	
RAM:	Test Server Minimum 2 GB	
	Production Server Minimum 4 GB	
Disk Space:	/ (root) Minimum 24 GB	
	/var/lib/Kiwi Minimum 10 GB	

Network Requirements

- The Uyuni Server requires a reliable and fast WAN connection.
- The branch server requires a reliable WAN connection, to reach the Uyuni Server.
- If you are using a dedicated network, the branch server requires at least two network interfaces: one connected to the WAN with a reachable Uyuni Server, and one connected to the internal branch LAN.
- Terminals require a LAN connection to the branch server network.

POS Terminal Requirements

Table 4. Hardware Requirements for Terminals

Hardware	Recommended
RAM:	Minimum 1 GB for hosts that need to run OS images built with Kiwi (PXE booted or not)
Disk Space:	Disk space depends on size of the OS image

For more information on Uyuni for Retail POS terminals, see documentation on Uyuni Salt clients ([**Client-configuration > Client-config-overview >**]).

Install with the Unified Installer

Uyuni for Retail is a SUSE base product. This section describes how to install Uyuni for Retail from SUSE Linux Enterprise Server installation media with the Unified Installer.

Before you begin the installation, check that your environment meets the requirements at [Installation > General-requirements >].

Install Uyuni for Retail

Procedure: Installing Uyuni for Retail Server from a DVD Image

- 1. Boot your server from the installation image. In case of trouble, you might need to adjust the boot order in the BIOS.
- 2. When prompted, select Installation.
- 3. In the Language, Keyboard and Product Selection screen, check the SUSE Manager Server checkbox, and click [Next].

SUSE					
Language, Keyboard and Product Selection	Language English (US) Froduct to Install SUSE Linux Enterprise Server 15 SP2 Beta2 SUSE Linux Enterprise Server for SAP Applications 15 SUSE Linux Enterprise Server for SAP Applications 15 SUSE Linux Enterprise Server 4.1 SUSE Manager Prova 1.1 Alpha0 SUSE Manager Retail Branch Server 4.1	Keyboard Layout English (US) Keyboard Test 5 SP2 Beta2 SP2 Beta2	Abort	Back	Ţ.

- 4. Read and agree to the End User Licence Agreement, and click [Next].
- 5. In the Registration screen, check the Register System via scc.suse.com checkbox, enter your SUSE Customer Center credentials, and click [Next].
- 6. OPTIONAL: In the Add On Product screen, select any additional or add-on products you require, and click [Next].
- 7. In the System Role screen, check the SUSE Manager for Retail Server checkbox, and click [Next].

SUSE				
	System Roles are predefined use cases which tailor the system for the selected scenario.			
System Role	SUSE Manager Server Manager Server pattern LVM-based partition layout			
	SUSE Manager for Retail Server • Retail Server Pattern • Larger volume for terminal Images			
	O Minimal Minimal software selection for SUSE Linux Enterprise.			
Help Rejease Notes		Abort	Back	Next

- 8. In the Suggested Partitioning screen, accept the default values, or use the [Guided Setup] or [Expert Partitioner] options to customize your partitioning model, and click [Next].
- 9. In the Clock and Time Zone screen, enter your region and timezone, and click [Next].
- 10. In the Local Users screen, create a new user, and click [Next].
- 11. In the System Administrator "root" screen, create the "root" user, and click [Next].
- 12. In the Installation Settings screen ensure that SSH access is open. Review the settings and click [Install].

Procedure: Running the Installation Script on the Uyuni Server

- 1. Use SSH to access the command prompt of the Uyuni Server.
- 2. Run the installation script:

yast susemanager_setup

3. Follow the prompts to set up your account. Take note of the passwords you set, you will need them later on.

Continue with general Uyuni configuration and channel synchronization at [Installation > Server-setup >].

Install Uyuni for Retail Branch Server

Procedure: Installing the Branch Server from a DVD Image

1. Boot your server from the installation image. In case of trouble, you might need to adjust the boot order in the BIOS.

- 2. When prompted, select Installation.
- 3. In the Language, Keyboard and Product Selection screen, check the SUSE Manager Retail Branch Server checkbox, and click [Next].

SUSE.		
Language, Keyboard and Product Selection	Language English (US)	Keyboard Layout English (US)
	Product to Install SUSE Linux Enterprise Server 15 SP1 SUSE Linux Enterprise High Performance Computing 1: SUSE Linux Enterprise Real Time 15 SP1 SUSE Linux Enterprise Server for SAP Applications 15 S SUSE Linux Enterprise Desktop 15 SP1 SUSE Linux Enterprise Desktop 15 SP1 SUSE Manager Server 4.0 SUSE Manager Revery 4.0 SUSE Manager Retail Branch Server 4.0	
Help		Abo <u>r</u> t <u>B</u> ack <u>N</u> ext

- 4. Read and agree to the End User Licence Agreement, and click [Next].
- 5. In the **Registration** screen, check the **Register** System via scc.suse.com checkbox, enter your SUSE Customer Center credentials, and click [Next].
- 6. OPTIONAL: In the Add On Product screen, select any additional or add-on products you require, and click [Next].
- 7. In the System Role screen, check the SUSE Manager Proxy checkbox, and click [Next].

SUSE.	
	System Roles are predefined use cases which tailor the system for the selected scenario.
System Role	SUSE Manager Proxy Manager Proxy Manager Proxy Configure from Manager Server Minimal
	Minimal software selection fr SUSE Linux Enterprise.
Help Release Notes	Abo <u>r</u> t <u>B</u> ack <u>Next</u>

- 8. In the Suggested Partitioning screen, accept the default values, or use the [Guided Setup] or [Expert Partitioner] options to customize your partitioning model, and click [Next].
- 9. In the Clock and Time Zone screen, enter your region and timezone, and click [Next].
- 10. In the Local Users screen, create a new user, and click [Next].
- 11. In the System Administrator "root" screen, create the "root" user, and click [Next].
- 12. In the Installation Settings screen ensure that SSH access is open. Review the settings and click [Install].

Procedure: Configuring and Registering the Branch Server

- Create an activation key based on the SLE-Product-SUSE-Manager-Retail-Branch-Server-4.1-Pool base channel. For more information about activation keys, see [Clientconfiguration > Activation-keys >].
- 2. In the Child Channels listing, select the recommended channels by clicking the include recommended icon:
 - SLE-Module-Basesystem15-SP2-Pool for x86_64 SMRBS 4.1
 - SLE-Module-Basesystem15-SP2-Updates for x86_64 SMRBS 4.1
 - SLE-Module-Server-Applications15-SP2-Pool for x86_64 SMRBS 4.1
 - SLE-Module-Server-Applications15-SP2-Updates for x86_64 SMRBS 4.1
 - SLE-Product-SUSE-Manager-Retail-Branch-Server-4.1-Updates for x86_64
- 3. Use this activation key in Uyuni Proxy registration at [Installation > Proxy-registration >].
- Configure Uyuni Proxy. For more information on how to do this, see [Installation > Proxy-setup >].



The branch server must be configured as a Salt managed proxy.

Cobbler TFTP is not supported on Uyuni for Retail. Do not configure the susemanager-tftpsync-recv tool on a Uyuni for Retail Branch Server.

Install Uyuni Build Host

Build hosts are regular SUSE Linux Enterprise Server installations registered to Uyuni as Salt minions. For more information how to install and register salt minions to Uyuni, see [Client-configuration > Registration-overview >].

For how to prepare a build host from an already registered Salt minion, see administration:imagemanagement.pdf.


Supported base OS versions of Uyuni for Retail Build Hosts:

- SUSE Linux Enterprise Server12 SP3
- SUSE Linux Enterprise Server12 SP4
- SUSE Linux Enterprise Server11 SP3

Network Architecture

Uyuni for Retail uses a layered architecture:

- The first layer contains the Uyuni Server.
- The second layer contains one or more branch servers to provide local network and boot services. It also contains one or more build hosts.
- The final layer contains any number of deployed point-of-service terminals.



Branch servers should be physically located close to point-of-service terminals, such as in an individual store or branch office. We recommend you have a fast network connection between the branch server and

its terminals. Branch servers provide services for PXE boot, and act as an image cache, Salt broker, and proxy for software components (RPM packages). The branch server can also manage local networking, and provide DHCP and DNS services.


Uyuni for Retail Branch Servers are implemented as enhanced Uyuni Proxies. For technical background information on Uyuni Proxies, see [Installation > Install-proxy-uyuni >].

Branch Server Network Configuration

The branch server can operate in several different network configurations. The two most common configurations are a dedicated network, or a shared network.


Dedicated Network Architecture

The branch server has a dedicated network interface card and terminals use an isolated internal branch network. In this configuration, the branch server manages the internal network and provides DHCP, DNS, PXE, FTP, and TFTP services.



Shared Network Architecture

The branch server and the terminals are connected to the same network as the Uyuni server. In this configuration, the branch server is not required to manage a network (DHCP and DNS services), but acts as a PXE boot server and provides FTP and TFTP services.



Setting up

To set up an Uyuni for Retail environment, you will need to have already installed and configured Uyuni Server, have one or more Uyuni for Retail branch server, and one or more Uyuni build host.

This section covers how to configure your Uyuni for Retail environment, including: * Prepare POS images * Configure services on the branch server * Synchronize POS images to the branch servers

The very first time you set up an Uyuni for Retail environment, you will need to perform all three steps. You will need to revisit some of these steps later on as you are working with Uyuni for Retail.

For example, the first time you configure the branch server, you will need to have images prepared for synchronization. If you are configuring more than one branch server, you can use the same images across different branch servers.

If you have an existing environment, and need to build new images, you do not need to re-initialize the branches. You will need to synchronize the images, and can skip setting up the services on the branch server.

Usually, POS images are rebuild when updated packages are available, and synchronized to the branch servers before the update window opens.

Prepare and Build Terminal Images

For information about Uyuni image building, see [Administration > Image-management >].

Uyuni for Retail POS images are images specifically tailored for Uyuni for Retail environment and designed to be deployed using PXE booting mechanism.

POS Image Templates

As starting point, SUSE provides basic templates at https://github.com/SUSE/manager-build-profiles/tree/ master/OSImage. These templates need to be adapted for specific usecases, for example by including specific applications, configuration settings, and users.



By default, POS templates do not include a system user. You will not be able to login as a user to a system that has been installed with a SUSE provided template. However you can use Salt to manage clients without a system user. You can use Salt to install a system user after the terminal has been deployed.

SLES 11 SP 3 Terminals

POS Terminals based on SUSE Linux Enterprise Server 11 SP 3 can be deployed in much the same way as other terminals, with a few differences.

• You must use the SLES 11 template

• SLES 11 images need to be activated with the SLES11 SP3 i586 and SLEPOS 11 SP3 i586 channels



Ensure that SLES 11 images are built on the SLES 11 build host. Building on the incorrect build host will cause your build to fail.



If you are building images for SLES 11 using profiles from an HTTPS git repository that uses TLS 1.0 or greater, it will fail. SLES 11 does not support later versions of TLS. You will need to clone the repository locally to use it for building.

Configure Services on the Branch Server

Before you configure the branch server, ensure you have decided on networking topology, and know the minion ID of the branch server. For the information about the possible network topologies, see [**Retail > Retail-network-arch >**].

Configure branch server services from the Uyuni Server. The configuration is then applied to the selected branch server using Salt states. Uyuni Formulas with Forms functionality is used to configure branch server services, however there are multiple ways to configure them:

- Uyuni for Retail provided command line tool retail_branch_init
- Uyuni for Retail provided mass import command line tool retail_yaml
- Uyuni web UI and configuring formulas manually (for advanced users)

The branch server can be configured automatically using the retail_branch_init command, as shown in this section. If you prefer to manually configure the branch server, you can do so using formulas. For more information about formulas, see [**Retail - Retail-formulas-intro -**].

Procedure: Configuring Branch Server Formulas With a Helper Script

1. Branch server configuration is performed using the retail_branch_init command:

retail_branch_init <branch_server_minion_id>

This command will configure branch server formulas with default values and for shared networking topology. For dedicated network topology run this command:

retail_branch_init <branch_server_minion_id> --dedicated-nic <network_device>

You can customize network information as well, together with custom **branch prefix**. For example:

```
retail_branch_init <branch_server_minion_id> --dedicated-nic eth1 \
--branch-prefix B001 \
--server-domain <branch_server_subdomain> \
--branch-ip 192.168.86.1 \
--netmask 255.255.0
```

You can use the retail_branch_init --help command for additional options.

- 2. Verify that your changes have been configured correctly by checking the Uyuni WebUI branch server system formulas.
- 3. Apply highstate on the branch server. You can do this through the WebUI, or by running this command:

salt <branch_server_minion_id> state.apply

Similar results can be achieved by using mass import command line tool.

Procedure: Configuring Branch Server Formulas With a Mass Import Tool

1. Prepare branch specific YAML file:

For example, create branch.yaml file with content:

For more information about mass import tool, see [Retail > Retail-mass-config >].

2. Import branch information from YAML file to Uyuni

retail_yaml --from-yaml branch.yaml

- 3. Verify that your changes have been configured correctly by checking the Uyuni WebUI branch server system formulas.
- 4. Apply highstate on the branch server.



Both retail_branch_init and retail_yaml commands override existing configuration settings of the specified branch server.

After the initial configuration done by command line tools, branch server configuration can be further adjusted in Uyuni WebUI through branch server formulas.

Required System Groups

Uyuni for Retail requires system groups for terminals and servers. Manually create these system groups during installation:

- TERMINALS
- SERVERS

Additionally, you will need to create a system group for each branch server, and each terminal hardware type in your environment. For more information about hardware type groups, see [**Retail** > **Retail** deploy-terminals >].

Branch server groups are named after branch server prefixes, for example group name 80001 for branch server prefix 8001.

You can create system groups using the Uyuni WebUI. Navigate to **Systems > System Groups** and click [**Create System Group**].

For more information about system groups, see [Reference > Systems >].



Uyuni for Retail command line tools create required system groups and branch group automatically.

Synchronize Images to the Branch Server

The OS image you use on the Uyuni server must be synchronized for use to the branch server. You can do this with the Salt image-sync state, part of the Image Synchronization Formula.

Procedure: Synchronizing Images to the Branch Server

1. On the Uyuni server, run this command:

salt <branch_server_minion_id> state.apply image-sync

2. The image details will be transferred to /srv/saltboot on the branch server.

You can also set synchronization to run automatically on the branch server. Configure the image synchronization formula to apply the highstate regularly. For more information about Image Synchronization Formula, see [Salt > Formula-imagesync >].

Deploying Terminals

This section covers how to prepare your Uyuni for Retail installation for image deployment, and how to deploy terminals using network boot and other methods.

Deploy Terminals

When you have the Uyuni Server and Branch Server set up, you are ready to deploy point-of-service terminals by following these steps:

- 1. Create hardware type groups
- 2. Assign and configure the Saltboot formula for each hardware type group
- 3. Synchronize images to the branch server
- 4. Deploy images to the terminals

Each procedure is detailed in this section.

For other methods of booting terminals, including using a USB device, or booting over a wireless network, see [**Retail > Retail-deploy-terminals-other >**].

If you have many terminals, and would prefer this to be handled with a script, see [**Retail > Retail-mass-config >**].

Before terminals can be deployed, ensure you have prepared a Saltboot-based operating system image. For how to build OS images, see [Administration > Image-management >].



After you have registered new terminals, always check the Uyuni WebUI to ensure your terminals have connected successfully to the branch server, and not directly to the Uyuni Server by mistake.

Create A Hardware Type Group

Each terminal requires a specific hardware type, which contains information about the product name and terminal manufacturer. However, at the beginning, the Uyuni database does not have this information. To tell Uyuni what image to deploy on each terminal, you can set hardware type groups. After you have created your new hardware type group, you can apply the Saltboot formula to the group and configure it for your environment.

Hardware types allow you to group devices according to manufacturer and device name. Then, all devices of a particular type can be managed as one.

Empty profiles can be assigned to a hardware type group either before or after registration. If an empty profile is not assigned to a hardware type group before registration, it will be assigned to group that best matches the product information available to it.

For this procedure, you will require the system manufacturer name and product name for your terminal.

Procedure: Creating a Hardware Type Group

1. Determine the hardware type group name. Prefix the name with HWTYPE:, followed by the system manufacturer name and product name, separated by a hyphen. For example:

HWTYPE:POSVendor-Terminal1

- 2. In the Uyuni WebUI, navigate to Systems > System Groups, and click the [Create Group] button.
- 3. In the **Create System Group** dialog, create a new system group, using the hardware type group name you determined in step one of this procedure.



Only use colons, hyphens, or underscores in hardware type group names. Spaces and other non-alphanumeric characters will be removed when the name is processed.

Assign and Configure the Saltboot Formula for Each Hardware Type Group

Each hardware type group must have the Saltboot formula applied.

Procedure: Assigning the Saltboot Formula

- 1. Open the details page for your new hardware type group, and navigate to the Formulas tab.
- 2. Select the Saltboot formula and click [Save].
- 3. Navigate to the **Formulas > Saltboot** tab.
- 4. Configure the Saltboot formula according to the instructions in [Retail > Retail-formulas-intro >].

Synchronize Images to the Branch Server

Procedure: Synchronizing Images to the Branch Server

1. On the Uyuni server, run this command:

salt <branch_server_salt_id> state.apply image-sync

Using a SUSE Linux Enterprise Server11 SP3 32-bit based images

If you have 32-bit machines included in your branch, then you must use a 32-bit boot image as a default boot image.



If 32-bit boot image is not used as a default boot image, 32-bit terminals will be unable to boot and operate properly.

You can check the available boot images and their architecture from the command line:

salt <branch_server_salt_id> pillar.item boot_images

Output:

```
POS_Image_JeOS6-6.0.0:
arch:
x86_64
legacy-6.0.0:
arch:
i686
```

In this example, the legacy-6.0.0 boot image is 32-bit.

You can set the default boot image in the Image Synchronization formula on the branch server, by adding the chosen boot image name to the Default boot image field. For more information about Image Synchronization formula, see [Salt > Formula-imagesync >].

≡ SUSE _® Manager > systema		🕬 Q 🕜 systems selected 🖋 📥 admin 🚓 SUSE QA 😻 🕒
Search page C	a proxy.tf.local •	Delete System
 ff Home ∨ Systems ∧ Overview System List ∨ 	Deals Software Configuration Provisioning Groups Audt States Formulas Events Formulas Branch Network Ditigs <u>Branchards</u> Local Per Thips Wated Brid On-Nits page you can configure <u>Saft Tormulas</u> to administratly install and configure software.	٥
System Groups System Set Manager × Bootstrapping Visualization × Advanced Search	Control page you can conside a <u>can execute</u> to another any neural and consider sources Prov Next + Image Synchronize	ty Save Formuta ≠ Chear values
Activation Keys Stored Profiles Custam System Info Autoinstallation ~ Software Crashes Virtual Host Managers	Include Image Spectroscation in Highstate:	
양 Sait ~ 윤 Images ~ 양 Patches ~	Default bool image: POS_Image_b056_5LE114.0.0	
U Faitnes ·		

Deploy Images to the Terminals

When you have your bootstrap image ready, you can deploy the image to the terminals.

Procedure: Deploying Images to the Terminals

- 1. Power on your POS terminals.
- 2. The branch server will bootstrap the terminals according to the data you have provided.

Re-Deploy Images to the Terminals

You can instruct terminals to download and deploy images when they are restarted. This is achieved using a Salt state.

Procedure: Forcing a Terminal to Re-Deploy Images

1. On the Uyuni Server, at the command prompt, as root, apply this Salt state:

salt \$terminal_minion_id state.apply saltboot.force_redeploy

2. Restart the terminal to pick up the changes.

If your terminal encounters a problem with the file system or the partition table, you might need to remove the partition table and reformat the terminal.



Re-partitioning a terminal removes all data stored on the terminal hard disk, including any persistent partitions.

Procedure: Forcing a Terminal to Repartition the Hard Disk

1. On the Uyuni Server, at the command prompt, as root, apply this Salt state:

salt \$terminal_minion_id state.apply saltboot.force_repartition

2. Restart the terminal to pick up the changes.

Customize the Terminal Image Download Process

You can change the terminal boot process using Salt pillars. Two Salt pillars allow you to change the protocol and server used to download the image.

- The saltboot_download_protocol pillar specifies which protocol should be used to download the image to the terminal. This overrides the default protocol specified in the image pillar. Allowed values are http, https, ftp, or tftp.
- The saltboot_download_server pillar specifies which server to use to download the image. This overrides the default hostname specified in the image pillar.

Example: Changing the Saltboot Image Download Protocol

This example changes the protocol used for all terminals.

Edit the /srv/pillar/top.sls file:

```
base:
    '*':
        - saltboot_proto
```

Edit the /srv/pillar/\$branch_prefix.sls file:

```
saltboot_download_protocol: http
# can be http, https, ftp, tftp
```

Example: Changing the Saltboot Image Download Location

This example changes the download location for all terminals on a specified branch server.

Edit the /srv/pillar/top.sls file:

```
base:
    'minion_id_prefix:$branch_prefix':
        - match: grain
        - $branch_prefix
```

Edit the /srv/pillar/\$branch_prefix.sls file:

saltboot_download_server: \$download_server_fqdn



In this example, the download server must be prepared by the image_sync state before you begin.

Deploy Terminals - Other Methods

If you are not able to boot terminals from the network, you can create a live USB image and deploy terminals using a removable USB storage device. You can also bootstrap terminals across a wireless network.



Hardware type groups must be created and images must be synchronized before continuing. For more information, see [**Retail > Retail-deploy-terminals >**].



After you have registered new terminals, always check the Uyuni WebUI to ensure your terminals have connected successfully to the branch server, and not directly to the Uyuni Server by mistake.

Deploy Terminals with a Removable USB Device

If you do not want to boot terminals from the network, you can create a live USB image and deploy terminals using a removable USB storage device. This is useful if you cannot boot your terminals from the network, or if you do not have a local Uyuni for Retail branch server providing network services.

You can prepare a bootable USB device with the image and tools required to deploy a POS terminal using a remote Uyuni for Retail branch server. You can create the bootable USB device on the branch server directly, or on the Uyuni for Retail Server.



POS devices booted using the USB device are assigned to the Uyuni for Retail branch server that created the USB device.

Procedure: Creating a Bootable USB Device

1. On the Uyuni for Retail branch server, at the command prompt, as root, create the POS image. You need to specify the size of the image, in megabytes. Ensure you allow at least 300 MB:

```
salt-call image_sync_usb.create <usb image name> <size in MB>
```

2. Insert the USB device into the Uyuni for Retail branch server machine, and copy the image to the new location:

dd bs=1M if=<usb image name> of=<path to usb device>

When you have the image on the USB drive, check that the terminals you want to deploy allow local booting. You can check this by editing the Saltboot formula in the Uyuni for Retail WebUI. For more information about the Saltboot formula, see [Salt > Formula-saltboot >].

Procedure: Deploying Images to the Terminals using USB

- 1. Insert the USB device into the terminal.
- 2. Power on the POS terminal.
- 3. Boot from the USB device to begin bootstrapping.

Bootstrap Terminals over a Wireless Network

For terminals that cannot be connected directly to the physical network, you can bootstrap them over a wireless network. Wireless networks do not support PXE booting, so you must perform the initial booting and initialization of the wireless connection on the terminal using a USB device.

For more information about using USB devices to boot, see [Retail > Retail-deploy-terminals-other >].



Bootstrapping across a wireless network could expose a security risk if you are using encrypted OS images. The boot **initrd** image and the partition that contains **/etc/salt** must be stored unencrypted on the terminal. This allows Uyuni for Retail to set up the wireless network. If this breaches your security requirements, you will need to use a separate production network, with network credentials managed by Salt, so that credentials are not stored on the terminal unencrypted.

Before you begin, you need to have created a bootable USB device. Ensure that the OS image you use to create the USB device has the dracut-wireless package included. For more information about using USB devices to boot, see [Retail > Retail-deploy-terminals-other >].

When you have created the USB device, you need to provide the wireless credentials to the terminal. You can do this in a number of ways:

• Directly during image build.

- Add it to the **initrd** file on the branch server.
- During terminal booting, using the kernel command line.

Procedure: Providing Wireless Credentials During Image Build

- 1. Ensure that the dracut-wireless package is included in the image template.
- 2. Set the wireless credentials by creating or editing the etc/sysconfig/network/ifcfg-wlan0 file to the image template, with these details:

ALLOW_UPDATE_FROM_INITRD
WIRELESS_ESSID=<wireless network name>
WIRELESS_WPA_PSK=<wireless network password>

If you want to use different credentials for bootstrapping to what is used during normal operation, you can remove the ALLOW_UPDATE_FROM_INITRD line.

- 3. Build the image.
- 4. Prepare a USB device using this image, and boot the terminal. For more information about using USB devices to boot, see [**Retail Retail-deploy-terminals-other ->**].

Procedure: Providing Wireless Credentials with initrd

 Set the wireless credentials by creating or editing the etc/sysconfig/network/ifcfg-wlan0 file, with these details:

```
# ALLOW_UPDATE_FROM_INITRD
WIRELESS_ESSID=<wireless network name>
WIRELESS_WPA_PSK=<wireless network password>
```

2. Copy the file to **initrd** on the branch server:

```
echo ./etc/sysconfig/network/ifcfg-wlan0 | cpio -H newc -o | gzip >>
/srv/saltboot/boot/initrd.gz
```

3. Check that the terminals you want to deploy allow local booting. You can check this by editing the Saltboot formula in the Uyuni for Retail WebUI. For more information about the Saltboot formula, see [Salt > Formula-saltboot >].

Procedure: Providing Wireless Credentials During Terminal Boot

- 1. Mount the USB device on the terminal, and boot from it.
- 2. Append these commands to the kernel boot parameters:

WIRELESS_ESSID=<wireless_network_name> WIRELESS_WPA_PSK=<wireless_network_password>

Change Wireless Credentials

After you have set the wireless credentials, you can change them as needed. The way to do this is different if you use one company-wide network, or if you have each branch server on its own separate network.

Procedure: Changing Wireless Credentials for Single Network

- 1. Rebuild the boot image with updated credentials.
- 2. Recreate the bootable USB device based on the new boot image.
- 3. Boot terminal from new USB device.

Procedure: Changing Wireless Credentials for Multiple Networks

1. In the /srv/salt/ directory, create a salt state called update-terminal-credentials.sls, and enter the new wireless network credentials:

```
/etc/sysconfig/network/ifcfg-wlan0
file.managed:
    contents: |
        WIRELESS_ESSID=<wireless_network_name>
        WIRELESS_WPA_PSK=<wireless_network_password>
# regenerate initrd
    cmd.run:
    - name: 'mkinitrd'
```

2. Apply the Salt state to the terminal:

salt <terminal_salt_name> state.apply update-terminal-credentials



If you are using a separate network for the boot phase, the managed file might need to be renamed, or extended to /etc/sysconfig/network/initrd-ifcfg-wlan0.

Use Multiple Wireless Networks

You can configure terminals to use a different set of wireless credentials during the boot process, to what they use during normal operation.

If you provide wireless credentials using initrd files, you can create two different files, one for use during boot called initrd-ifcfg-wlan0, and the other for use during normal operation, called ifcfg-wlan0.

Alternatively, you can use custom Salt states to manage wireless credentials with saltboot-hook.

First of all, you need to set the wireless details for normal operation. This will become the default settings. Then you can specify a second Salt state with the wireless details for use during the boot procedure.

Procedure: Using Different Wireless Credentials for Production Network

1. Write a custom Salt state named /srv/salt/saltboot_hook.sls containing the wireless details for normal operation. This Salt state is applied by Saltboot after the system image is deployed.




The boot phase supports only WPA2 PSK wireless configuration. Salt-managed production configuration supports all features supported by all major operating systems.

Saltboot Diagram

The saltboot process involves the Uyuni Server, a terminal running the saltboot **initrd**, and the branch server providing the saltboot services to the terminal.

This sequence diagram explains how the three components interact with each other to boot a Uyuni for Retail terminal.



Terminal Names

Terminals can be named according to certain parameters, which can make it easier to match the physical device with its record in the Uyuni WebUI.

Naming schemes available are Hostname, FQDN, and HWType. Naming scheme can be selected in the Branch Network formula. For more information, see [Salt > Formula-branchnetwork >].

By default, terminals are named according to the Hostname naming scheme with the HWType scheme as a fallback.

Naming by HWType

Terminal names that are derived from the hardware type use this format:

BranchID.Manufacturer-ProductName-SerialNumber-UniqueID

For example:

B002.TOSHIBA-6140100-41BA03X-c643

The BranchID is the unique identifier for the branch server that the terminal is connected to. You can configure this value in the [Salt > Formula-branchnetwork >] settings for the branch server. You can disable this prefix by toggling the Do not prefix salt client ID with Branch ID checkbox in the [Salt > Formula-branchnetwork >].

The Manufacturer, ProductName, and SerialNumber are provided by the terminal hardware BIOS. If the terminal does not provide a serial number, it will be omitted from the terminal name.

The UniqueID is the first four characters of a generated machine identification number. Added unique ID is a requirement for successful terminal deployment. Without unique ID, subsequent terminal registration will fail.

Naming by Hostname

Terminal names that are derived from the hostname use this format:

BranchID.Hostname-UniqueID

For example:

B002.terminal-c643

The BranchID is the unique identifier for the branch server that the terminal is connected to. You can configure this value in the [Salt > Formula-branchnetwork >] settings for the branch server. You can disable this prefix by toggling the Do not prefix salt client ID with Branch ID checkbox in the [Salt > Formula-branchnetwork >].

The **Hostname** is the plain hostname (without domain part) of the terminal.

The UniqueID is the first four characters of a generated machine identification number. You can disable this behaviour by toggling the Do not append unique suffix to the salt client ID checkbox in the [Salt > Formula-branchnetwork >].

Naming by **FQDN**

Terminal names that are derived from the Fully Qualified Domain Names (FQDN) use this format:

BranchID.FQDN-UniqueID

For example:

B002.terminal.example.com-c643

The BranchID is the unique identifier for the branch server that the terminal is connected to. You can configure this value in the [Salt > Formula-branchnetwork >] settings for the branch server. You can disable this prefix by toggling the Do not prefix salt client ID with Branch ID checkbox in the [Salt > Formula-branchnetwork >].

The FQDN is the fully-qualified domain name of the terminal.

The UniqueID is the first four characters of a generated machine identification number. You can disable this behaviour by toggling the Do not append unique suffix to the salt client ID checkbox in the [Salt > Formula-branchnetwork >].

Assign Hostnames to Terminals

If you want terminal names to be derived from the hostname, you will need to ensure your terminals have a static hostname. This requires a static IP address to be able to resolve the static hostname.

There are a number of different ways to assign hostnames to terminals. This section describes how to do this when DNS and DHCP services are managed by the branch server.

Procedure: Assigning IP Address and Hostname with Formulas

- In the DHCP formula settings, navigate to Hosts with Static IP Address and click [Add Item]. For more information on the DHCP formula, see [Salt > Formula-dhcpd >].
- 2. In the **Hostname** field, type the hostname of the branch server.

- 3. In the IP Address field, type the static IP address for the terminal. Ensure the IP address is within the range used by the branch server.
- 4. In the Hardware Type and Address field, type the hardware type and address in this format:

ethernet <terminal_MAC_address>

- 5. OPTIONAL: For multiple terminals, click [Add Item] and fill in the details for each terminal.
- 6. Click [Save Formula] to save the changes.
- In the Bind formula settings, navigate to the A records of the appropriate non-reverse zone, and click
 [Add Item]. For more information on the bind formula, see [Salt > Formula-bind >].
- 8. In the Hostname field, type the hostname of the branch server.
- 9. In the IP Address field, type the static IP address you assigned to the terminal in the DHCP formula settings.
- 10. OPTIONAL: For multiple terminals, click [Add Item] and fill in the details for each terminal.
- 11. Click [Save Formula] to save the changes.
- 12. Apply the highstate on the branch server to apply the changes.



If the terminal was previously registered using a name based on the hardware type instead of the hostname, you will need to delete the previous registration. When you re-register the terminal, use the new terminal name.

Procedure: Assigning IP Address and Hostname with YAML

1. At the command prompt on the branch server, export a YAML configuration file:

retail_yaml --to-yaml retail.yaml

- 2. Open the YAML file and navigate to the end of the branch server section. Add a new terminals section if it does not already exist.
- 3. Add the IP address, MAC address, and hardware type for the terminal, using this format:

```
$hostname:
    IP: <IP_Address>
    hwAddress: <MAC_Address>
    hwtype: <HWTYPE_Group_name_without_HWTYPE:_prefix>
```

4. Import the modified YAML file:

```
retail_yaml --from-yaml retail.yaml
```

5. Apply the highstate on the branch server to apply the changes.



If the terminal was previously registered using a name based on the hardware type instead of the hostname, you will need to delete the previous registration. When you re-register the terminal, use the new terminal name.

For more information about using YAML configuration files, see [Retail > Retail-mass-config >].

Offline Use

If the Uyuni Server is offline, you can still perform some operations on the terminals. This is useful if the connection between the branch server and the Uyuni Server is unstable or has low bandwidth. This feature uses caching to perform updates.



Offline features and features relying on caching are available only for Uyuni Server 4.0 and above.

Offline Terminal Reboot

If the Uyuni Server is offline, and a terminal is rebooted, it will fall back to a previously installed image.

This will occur in these situations:

- If the Saltboot formula has not started within a specified time (default value is 60 seconds).
- If the terminal does not acknowledge that the Saltboot formula has started.
- If the root partition is specified on the kernel command line (handled by the PXE formula), is mountable (and is not encrypted), and contains /etc/ImageVersion (which is created by Kiwi).

You can adjust the timeout value by changing the SALT_TIMEOUT kernel parameter. The parameter is measured in seconds, and defaults to 60.

SALT_TIMEOUT = 60

For more about kernel parameters, see [Salt > Formula-pxe >].

Cached Terminal Updates

If there is low bandwidth between the branch server and the terminal, or for optimization of terminal update process, POS images can be cached in advance on the terminal and the upgrade performed on the terminals later on.

This functionality requires the terminal to have a dedicated service partition. A service partition is a partition mounted as /srv/saltboot. This partition must be created before the system partition and large enough to store a POS image. To ensure that terminals will always have such a partition, use the

Saltboot formula for terminal hardware type to specify the partition details. For more information, see [Salt > Formula-saltboot >].

When the service partition is set up on the terminal, a POS image can be downloaded in advance by applying the saltboot.cache_image state:

salt \$TERMINALID state.apply saltboot.cache_image

This can be done regularly to ensure that terminals always have an uptodate POS image downloaded.

When the terminal is rebooted and an uptodate POS image is found in the service partition, the terminal will automatically use this cached image for system redeployment.

Rate Limiting Terminals

Salt is able to run commands in parallel on a large number of terminals. This can potentially create heavy load on your infrastructure. You can use rate-limiting parameters to control the load in your environment.

For more information about rate limiting on terminals, see [Salt > Salt-rate-limiting >].

Troubleshooting

Sometimes when attempting to reboot a terminal after attempting to apply the Saltboot formula, the terminal will hang at the boot screen. This can be caused by a presence ping timeout value being set at a value that is too low. You can adjust the presence ping timeout value to fix this problem.

For more information about rate limiting on terminals, see [Salt > Salt-rate-limiting >].

Introduction to Retail Formulas

Formulas are pre-written Salt states, that are used to configure your Uyuni for Retail installation.

You can use the Uyuni WebUI to apply common Uyuni formulas. For the most commonly used formulas, see [Salt > Formulas-intro >].

All formulas must be accurately configured for your Uyuni for Retail installation to function correctly. If you are unsure of the correct formula configuration details, run the retail_branch_init command before you begin to create the recommended formula configuration. You can then manually edit the formulas as required.

Branch Server Formulas

Branch servers are configured using formulas. Formulas can be configured using Uyuni WebUI, or the Uyuni XMLRPC API. To fully configure Uyuni for Retail, these formulas need to be enabled and configured on the branch server:

- Branch network formula, see [Salt > Formula-branchnetwork >]
- Bind formula, see [Salt > Formula-bind >]
- DHCPD formula, see [Salt > Formula-dhcpd >]
- PXE formula, see [Salt > Formula-pxe >]
- TFTP formula, see [Salt > Formula-tftpd >]
- VSFTP formula, see [Salt > Formula-vsftpd >]

Optionally, you can also enable the image synchronization formula. For more information, see [Salt > Formula-imagesync >].



Badly configured formulas can result in the branch server failing to work as expected. Due to the generic nature of formulas it is difficult to do overall validation. We recommend that you configure the branch server using the Uyuni for Retail command line utilities, and use individual formula settings for further tuning if required. For more information, see [**Retail > Retail-install-setup >**].



If a formula uses the same name as an existing Salt state, the two names will collide, and could result in the formula being used instead of the state. Always check the names of states and formulas to avoid name collisions.

When you have made changes to your formula, ensure you apply the highstate. The highstate propagates your changes to the appropriate services.

Partitioning and Image Deployment Formula

Use the Saltboot formula to specify disk partitioning, and to select which image should be deployed. For more information about the Saltboot formula, see [Salt > Formula-saltboot >].

Administration

This sections contains notes on administering your Uyuni for Retail installation. For general administration tasks, see the Uyuni documentation at https://documentation.suse.com/suma/4.0/.

Mass Configuration

Mass configuration is possible with branch servers and terminals.

Branch Server Mass Configuration

Branch servers are configured individually using formulas. If you are working in an environment with many branch servers, you might find it easier to configure branch servers automatically with a pre-defined configuration file, rather than configuring each one individually.

Before working with the mass configuration tool, back up the existing branch servers configuration.

The Mass configuration tool overwrites the existing configuration with data specified in the provided YAML file.

The Mass configuration tool does not support all possible formula configurations. Always make sure on a small sample, that the mass configuration tool can configure systems as expected.

Configure Multiple Branch Servers

Configuring multiple branch servers requires the python-susemanager-retail package, which is provided with Uyuni for Retail. Install the python-susemanager-retail package on the Uyuni server.

Procedure: Configuring Multiple Branch Servers

- 1. Create a YAML file describing the infrastructure you intend to install. For an example YAML file, see retail-mass-config-yaml.pdf.
- 2. On a clean Uyuni installation, import the YAML file you have created:

retail_yaml --from-yaml filename.yaml

See the retail_yaml --help output for additional options.

- 3. In the Uyuni WebUI, check that your systems are listed and displaying correctly, and the formulas you require are available.
- 4. Create activation keys for each of your branch servers, connect them using bootstrap, and configure them as proxy servers. For more information, see [**Retail Retail-install-unified -**].



5. In the **States** tab, click [**Apply Highstate**] to deploy your configuration changes for each branch server.

If you need to change your configuration, you can edit the YAML file at any time, and use the retail_yaml --from-yaml command to upload the new configuration.

Use empty profiles together with activation keys to onboard all the systems of your infrastructure. Use an activation key to assign the channels listed in **[Retail -> Retail-install-setup ->]**.

Terminal Mass Configuration

If you are working in an environment with many terminals, you might find it easier to configure the terminals automatically with a pre-defined configuration file, rather than configuring each terminal individually.

You will need to have your infrastructure planned out ahead of time, including the IP addresses, hostnames, and domain names of branch servers and terminals. You will also require the hardware (MAC) addresses of each terminal.



The settings specified in the configuration file cannot always be successfully applied. In cases where there is a conflict, Uyuni will ignore the request in the file. This is especially important when designating hostnames. You should always check that the details have been applied as expected after using this configuration method.

Configure Multiple Terminals

Procedure: Configuring Multiple Terminals

- 1. Create a YAML file describing the infrastructure you intend to install, specifying the hardware address for each terminal. For an example YAML file, see retail-mass-config-yaml.pdf.
- 2. On a clean Uyuni installation, import the YAML file you have created:

retail_yaml --from-yaml filename.yaml

See the retail_yaml --help output for additional options.

- 3. In the Uyuni WebUI, check that your systems are listed and displaying correctly, and the formulas you require are available.
- 4. Create activation keys for each of your branch servers, connect them using bootstrap, and configure them as proxy servers. For more information, see [**Retail Retail-install-unified -**].
- 5. In the **States** tab, click [**Apply Highstate**] to deploy your configuration changes for each branch server.
- 6. Connect your terminals according to your infrastructure plan.

If you need to change your configuration, you can edit the YAML file at any time, and use the retail_yaml --from-yaml command to upload the new configuration.

Export Configuration to Mass Configuration File

If you already have a configuration that you would like to export to a YAML file, use:

retail_yaml --to-yaml filename.yaml

This can be a good way to create a basic mass configuration file. However, it is important to check the file before using it, because some mandatory configuration entries may be missing.



When you are designing your configuration and creating the YAML file, ensure the branch server ID matches the fully qualified hostname, and the Salt ID. If these do not match, the bootstrap script could fail.

Example YAML File for Mass Configuration

You can use the retail_yaml command to import configuration parameters from a manually prepared YAML file. This section contains YAML example file with comments.

Listing 1. Example: YAML Mass Terminal Configuration File

```
branches:
# there are 2 possible setups: with / without dedicated NIC
# with dedicated NIC
  branchserver1.branch1.cz:
                                  # salt ID of branch server
                                  # optional, default guessed from salt id
    branch_prefix: branch1
                                 # optional, default guessed from salt id
# optional, default guessed from salt id
    server name: branchserver1
    server_domain: branch1.cz
                                  # nic used for connecting terminals, default taken from hw
    nic: eth1
info in SUMA
    dedicated_nic: true
                                  # set to true if the terminals are on separate network
    salt_cname: branchserver1.branch1.cz
                                                 # hostname of salt master / broker for
terminals, mandatory
    configure_firewall: true
                                  # modify firewall configuration
    branch_ip: 192.168.2.1
                                  # default for dedicated NIC: 192.168.1.1
    netmask: 255.255.255.0
                                  # default for dedicated NIC: 255.255.255.0
    dyn_range:
                                  # default for dedicated NIC: 192.168.1.10 - 192.168.1.250
        - 192.168.2.10
        - 192.168.2.250
# without dedicated NIC
# the DHCP formula is not used, DHCP is typically provided by a router
# the network parameters can be autodetected if the machine is already connected to SUSE
Manager
                                  # salt ID of branch server
  branchserver2.branch2.cz:
    branch_prefix: branch2
                                  # optional, default guessed from salt id
                                  # optional, default guessed from salt id
# optional, default guessed from salt id
    server name: branchserver2
    server_domain: branch2.cz
    salt_cname: branchserver2.branch1.cz
                                                 # FQDN of salt master / broker for terminals,
mandatory
                                  # optional, default taken from SUMA data if the machine is
    branch_ip: 192.168.2.1
registered
    netmask: 255.255.255.0
                                  # optional, default taken from SUMA data if the machine is
registered
```

```
exclude formulas:
                                 # optional, do not configure listed formulas
                                 # without dedicated NIC the dhcp service is typically
       dhcp
provided by a router
    hwAddress: 11:22:33:44:55:66 # optional, required to connect pre-configured entry with
particular machine
                                  # during onboarding
    terminals:
                                      # configuration of static terminal entries
      hostname1:
                                      # hostname
        hwAddress: aa:aa:ab:bb:bb # required as unique id of a terminal
        IP: 192.168.2.50
                                      # required for static dhcp and dns entry
                                      # optional, alternative 1: configure terminal-specific
        saltboot:
pillar data
          partitioning:
                                      # partitioning pillar as described in saltboot
documentation
            disk1:
              device: /dev/sda
              disklabel: msdos
              partitions:
                p1:
                  flags: swap
                  format: swap
                  size_MiB: 2000.0
                p2:
                  image: POS_Image_JeOS6
                  mountpoint: /
              type: DISK
      hostname2:
                                      # hostname
        hwAddress: aa:aa:abb:bb:cc # required as unique id of a terminal
                                      # required for static dhcp and dns entry
        IP: 192.168.2.51
        hwtype: IBMCORPORATION-4838910 # optional, alternative 2: assign the terminal to
hwtype group
        # if neither of hwtype nor saltboot is specified, a group is assigned according to
hwtype
        # reported by bios on the first boot
hwtypes:
  IBMCORPORATION-4838910:
                                # HWTYPE string (manufacturer-model) as returned by bios
    description: 4838-910
                                 # freetext description
    saltboot:
      partitioning:
                                 # partitioning pillar as described in saltboot documentation
        disk1:
          device: /dev/sda
          disklabel: msdos
          partitions:
            p1:
              flags: swap
              format: swap
size_MiB: 1000.0
            p2:
              image: POS_Image_JeOS6
              mountpoint: /
          type: DISK
  TOSHIBA-6140100:
    description: HWTYPE:TOSHIBA-6140100
    saltboot:
      partitioning:
        disk1:
          device: /dev/sda
          disklabel: msdos
          partitions:
            p1:
              flags: swap
              format: swap
              size_MiB: 1000.0
            p2:
              image: POS_Image_JeOS6
              mountpoint: /
          type: DISK
```

Delta Images

If you have very large images that you need to synchronize to the branch server, you can use delta images to save network bandwidth.

A delta image contains only the differences between two regular images. If there are only a few changes between two images, the delta image can be very small. Synchronizing a delta image to the branch consumes less network bandwidth but it requires some extra hardware resources on the branch server to rebuild the installable image.

Building Delta Images

The **retail_create_delta** tool creates a delta image on the Uyuni server. The tool uses **xdelta3** internally.

Use the name and the version strings of the target and the source image as parameters to the command. The format of the parameters must be <NAME>-<VERSION> and they must correspond to the image names and versions available in the pillar. For example, if the pillar contains:

```
images:
POS_Image_JeOS6:
    6.0.0:
    6.0.1:
    POS_Image_Graphical6:
    6.0.0:
    ...
```

Then the retail_create_delta command is:

retail_create_delta POS_Image_JeOS6-6.0.1 POS_Image_JeOS6-6.0.0

This command will generate the delta image between version 6.0.0 and version 6.0.1. The resulting delta file is saved in /srv/www/os-images and the corresponding pillar file in /srv/susemanager/pillar_data/images/.

Tuning Delta Generation

Performance tuning is possible with the -B <VALUE> option, which is passed to xdelta3. With higher values you achieve smaller deltas at the cost of higher memory requirements. For more information, see the xdelta3 documentation (man xdelta3).

Image Synchronizing to the Branch Server

When an image is synchronized to the branch server, the **image-sync-formula** first checks whether the source image is available on the branch server. If the source image is available, the delta will be

downloaded to save network bandwidth.

Retail Migration

For migrating Uyuni for Retail to the latest version, see the Uyuni upgrade instructions.

Upgrade Uyuni for Retail Branch Server

This section describes upgrading a Uyuni for Retail Branch Server to the next SP (service pack).

Uyuni for Retail Branch Server is a client system such as a Uyuni Proxy with additional Uyuni for Retail features.



Upgrade the Uyuni Server before starting the Uyuni for Retail upgrade.

Procedure: Upgrading the Uyuni for Retail Branch Server

- 1. For general information about upgrading a proxy client, see [Upgrade > Proxy-intro >].
- 2. After the proxy upgrade is complete, apply the highstate on the Uyuni for Retail Branch Server. When applying the highstate, the retail functionality will also be updated.

What Next?

This document covers only a sub-section of information about your Uyuni for Retail installation. If you need further information or support, try one of these options.

More Documentation

For Uyuni documentation, visit https://documentation.suse.com/suma/4.0/.

For legacy SUSE Linux Enterprise Point of Service documentation, see https://documentation.suse.com/ sle-pos/11-SP3/. For legacy Uyuni for Retail documentation, see https://documentation.suse.com/sumaretail/3.2/. Note, however, that Uyuni for Retail documentation supersedes this information.

Support

For personalized support, log in to your SUSE Customer Center account at https://scc.suse.com/login.

For assistance with planning and installing your Uyuni for Retail environment, contact the SUSE Consulting team.

GNU Free Documentation License

Copyright © 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a worldwide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections

then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See http://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled{ldquo}GNU Free Documentation License{rdquo}.

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with...Texts." line with this:

with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.